

1

# Notice of variation and consolidation with introductory note

The Environmental Permitting (England & Wales) Regulations 2016

Veolia ES Leeds Limited

Leeds Recycling and Energy Recovery Facility Former Wholesale Market Site Cross Green Leeds LS9 0RJ

#### Variation application number

EPR/GP3334CX/V005

#### **Permit number**

EPR/GP3334CX

## Leeds Recycling and Energy Recovery Facility Permit number EPR/GP3334CX

#### Introductory note

#### This introductory note does not form a part of the notice

Under the Environmental Permitting (England & Wales) Regulations 2016 (schedule 5, part 1, paragraph 19) a variation may comprise a consolidated permit reflecting the variations and a notice specifying the variations included in that consolidated permit.

This variation has been issued to update the permit following a statutory review of the permits in the industry sector for incineration. The Industrial Emissions Directive (IED) came into force on 7th January 2014 with the requirement to implement all relevant Best Available Techniques (BAT) conclusions as described in the Commission Implementing Decision. The BAT conclusions for incineration were published on 03 December 2019 in the Official Journal of the European Union (L323) following a European Union wide review of BAT, implementing decision 2017/2117/EU of 21 November 2017.

The schedules specify the changes made to the permit. Schedule 1 of the notice specifies the conditions that have been varied and schedule 2 comprises a consolidated permit which reflects the variations being made. All the conditions of the permit have been varied and are subject to the right of appeal.

#### Brief description of the process

This permit controls the operation of a waste incineration plant. The relevant listed activity is S5.1 A1(b). The permit implements the requirements of the EU Directives on Industrial Emissions and Waste.

The main features of the permit are as follows:

Furnace technology	Moving Grate
Number of lines	1
Principal waste type	Municipal
Stack height	75 m
Permitted plant capacity	214,000 tonnes per year for pre-treatment 190,000 tonnes per year for incineration
Electrical generation capacity	15 MWe

The Installation consists of one incineration line with a capacity of 22.6 tonnes per hour. The Installation accepts mainly municipal solid waste and also some commercial wastes.

Waste is delivered in covered vehicles or containers to the tipping hall, where it is tipped into a mechanical pre-treatment (MPT) area or directly into the waste bunker via a reception hall and an intermediate bunker. The MPT removes metals, treatment consists of shredders, screens, magnets and eddy current separators. The treatment is designed to remove waste for recycling, create a more homogeneous feedstock for improved combustion and to remove of plastics to reduce the amount of reagents required in the flue gas treatment system. After treatment waste is transported by conveyor to the waste bunker.

The waste in the bunker is mixed with a crane to prevent anaerobic conditions and hence odour.

Waste is loaded into the incinerator, using the crane, via the feed hopper. The waste is fed onto the moving grate where it is burned in a reverse acting grate system. Primary and secondary air supply is controlled to ensure good combustion conditions. A temperature of 850°C for at least 2 seconds is achieved.

Un-burnt material is called bottom ash. The bottom ash is quenched in water and ferrous metals removed by a magnet. The bottom ash is then transported by conveyor to an indoor storage area. The bottom ash is then sent off site to a suitably licensed waste treatment facility for recovery where possible.

Combustion air is treated to reduce the level of pollutants emitted. SNCR, using dry urea, is used for oxides of nitrogen, bag filters for particulate matter, dry lime injection for acid gases and activated carbon injection for dioxins and mercury. After the clean up, the gases are emitted to air through a 75m high stack.

The bag filters collect Air Pollution Control (APC) residues which are transferred to a silo and then to a tanker for removal from site. Sealed bags can sometimes be used instead of the tanker. APC residues are sent for off-site disposal or for use in waste neutralisation at a suitably licensed facility.

Steam is generated in a boiler and used to drive a turbine to generate electricity. Approximately 11MW can be exported to the grid. The Installation also supplies heat to the Leeds district heating scheme.

Process water and rainwater run-off from potentially contaminated areas is collected in a waste water pit and re-used in the process. During normal operations there are no emissions to sewer from the pit. During operation outside normal parameters, water from waste water pit can be emitted to sewer after solids separation and pH adjustment. Boiler maintenance or shut-down can create large waste water flows and mean the need for discharge to sewer.

Clean rainwater run off from the roof and perimeter roads is managed through a Sustainable Urban Drainage system to sewer.

The permit also includes a standard rules waste transfer station (SR2008No1 75kte).

The status log of a permit sets out the permitting history, including any changes to the permit reference number.

Status log of the permit		
Description	Date	Comments
Application	Duly made	
EPR/GP3334CX/A001	02/08/12	

Status log of the permit			
<b>Description</b> Date		Comments	
Schedule 5 notice (dated 19/11/12)	Response received 07/01/13		
Additional information received	08/01/13	Odour model input files	
Additional information received	15/02/13	Additional information on odour assessment	
Additional information received	20/02/13	Odour model input files	
Permit determined EPR/GP3334CX	18/07/13		
Variation application EPR/GP3334CX/V002	Duly made 04/02/16	Application for a variation to extend the installation boundary to include the Leeds Pro-Fibre installation area which is a technically linked activity.	
Variation determined EPR/GP3334CX/V002	02/08/16	Varied permit issued.	
Variation application EPR/GP3334CX/V003	Duly made 15/05/17	Application for a variation to change the emission limit value (ELV) for carbon monoxide from half-hour average to the 10 minute average.	
Variation determined EPR/GP3334CX/V003	21/06/17	Varied permit issued.	
Variation application EPR/GP3334CX/V004	Duly made 19/11/20	Application to increase the annual waste throughput through the incinerator line from 179,580 to 190,000 tonnes.	
Variation determined EPR/GP3334CX/V004	09/12/20	Varied and consolidated permit issued in modern format.	
Permit review EPR/GP3334CX/V005	Environment Agency initiated variation	Statutory review of permit. BAT Conclusions published 03 December 2019.	
Variation determined EPR/GP3334CX/V005	15/03/22		

Other Part A installation permits relating to this installation			
Operator Permit number Date of issue			
Veolia ES UK Limited	EPR/BP3931RJ	02/08/16	

End of introductory note

#### Notice of variation and consolidation

#### The Environmental Permitting (England and Wales) Regulations 2016

The Environment Agency in exercise of its powers under regulation 20 of the Environmental Permitting (England and Wales) Regulations 2016 varies

#### Permit number

EPR/GP3334CX

#### Issued to

Veolia ES Leeds Limited ("the operator")

whose registered office is

210 Pentonville Road London N1 9JY

company registration number 07876913

to operate part of a regulated facility at

Leeds Recycling and Energy Recovery Facility Former Wholesale Market Site Cross Green Leeds LS9 0RJ

to the extent set out in the schedules.

The notice shall take effect from 15/03/2022

Name	Date
Philip Lamb	15/03/2022

Authorised on behalf of the Environment Agency

#### Schedule 1

All conditions have been varied by the consolidated permit as a result of an Environment Agency initiated variation.

#### Schedule 2 – consolidated permit

Consolidated permit issued as a separate document.

#### **Permit**

#### The Environmental Permitting (England and Wales) Regulations 2016

#### **Permit number**

#### EPR/GP3334CX

This is the consolidated permit referred to in the variation and consolidation notice for application EPR/GP3334CX/V005 authorising,

Veolia ES Leeds Limited ("the operator"),

whose registered office is

210 Pentonville Road London N1 9JY

company registration number 07876913

to operate part of a regulated facility at

Leeds Recycling and Energy Recovery Facility Former Wholesale Market Site Cross Green Leeds LS9 0RJ

to the extent authorised by and subject to the conditions of this permit.

Under regulation 27(2) of the Regulations, standard rules SR2008No 1 75kte are conditions of this permit.

Name	Date
Philip Lamb	15/03/2022

Authorised on behalf of the Environment Agency

#### **Conditions**

#### 1 Management

#### 1.1 General management

- 1.1.1 The operator shall manage and operate the activities:
  - (a) in accordance with a written management system that identifies and minimises risks of pollution, including those arising from operations, maintenance, accidents, incidents, non-conformances, closure and those drawn to the attention of the operator as a result of complaints; and
  - (b) using sufficient competent persons and resources.
  - (c) referenced in schedule 1, table S1.1 (AR1), from 03/12/2023, in accordance with a written other than normal operating conditions (OTNOC) management plan.
- 1.1.2 Records demonstrating compliance with condition 1.1.1 shall be maintained.
- 1.1.3 The operator shall review the written management system at least every 3 years or otherwise as requested by the Environment Agency.
- 1.1.4 Any person having duties that are or may be affected by the matters set out in this permit shall have convenient access to a copy of it kept at or near the place where those duties are carried out.

#### 1.2 Energy efficiency

- 1.2.1 The operator shall:
  - (a) take appropriate measures to ensure that energy is recovered with a high level of energy efficiency and energy is used efficiently in the activities.
  - (b) review and record at least every four years whether there are suitable opportunities to improve the energy efficiency of the activities; and
  - (c) take any further appropriate measures identified by a review.

#### 1.3 Efficient use of raw materials

- 1.3.1 The operator shall:
  - (a) take appropriate measures to ensure that raw materials and water are used efficiently in the activities;
  - (b) maintain records of raw materials and water used in the activities;
  - review and record at least every four years whether there are suitable alternative materials that could reduce environmental impact or opportunities to improve the efficiency of raw material and water use; and
  - (d) take any further appropriate measures identified by a review.

## 1.4 Avoidance, recovery and disposal of wastes produced by the activities

- 1.4.1 The operator shall take appropriate measures to ensure that:
  - (a) the waste hierarchy referred to in Article 4 of the Waste Framework Directive is applied to the generation of waste by the activities; and
  - (b) any waste generated by the activities is treated in accordance with the waste hierarchy referred to in Article 4 of the Waste Framework Directive; and
  - (c) where disposal is necessary, this is undertaken in a manner which minimises its impact on the environment.
- 1.4.2 The operator shall review and record at least every four years whether changes to those measures should be made and take any further appropriate measures identified by a review.

#### 1.5 Multiple operator installations

1.5.1 Where the operator notifies the Environment Agency under condition 4.3.1 (a) or 4.3.1 (c), the operator shall also notify without delay the other operator of the installation of the same information.

#### 2 Operations

#### 2.1 Permitted activities

- 2.1.1 The operator is only authorised to carry out the activities specified in schedule 1 table S1.1 (the "activities").
- 2.1.2 Waste authorised by this permit shall be clearly distinguished from any other waste on the site.

#### 2.2 The site

2.2.1 The activities shall not extend beyond the site, being the land shown edged in green on the site plan at schedule 7 to this permit, which is within the area edged in red on the site plan that represents the extent of the installation covered by this permit and that of the other operator of the installation.

#### 2.3 Operating techniques

- 2.3.1 The activities shall, subject to the conditions of this permit, be operated using the techniques and in the manner described in the documentation specified in schedule 1, table S1.2, unless otherwise agreed in writing by the Environment Agency.
- 2.3.2 If notified by the Environment Agency that the activities are giving rise to pollution, the operator shall submit to the Environment Agency for approval within the period specified, a revision of any plan specified in schedule 1, table S1.2 or otherwise required under this permit which identifies and minimises the risks of pollution relevant to that plan, and shall implement the approved revised plan in place of the original from the date of approval, unless otherwise agreed in writing by the Environment Agency.
- 2.3.3 Any raw materials or fuels listed in schedule 2 table S2.1 shall conform to the specifications set out in that table.
- 2.3.4 Waste shall only be accepted if:
  - (a) it is of a type and quantity listed in schedule 2 tables S2.2 or S2.3; and
  - (b) it conforms to the description in the documentation supplied by the producer or holder.

- 2.3.5 Waste paper, metal, plastic or glass that has been separately collected for the purpose of preparing for re-use or recycling shall not be accepted. Waste from the treatment of these separately collected wastes shall only be accepted if incineration delivers the best environmental outcome in accordance with regulation 12 of the Waste (England and Wales) Regulations 2011.
- 2.3.6 Separately collected fractions other than those listed in condition 2.3.5 shall not be accepted unless they are unsuitable for recovery by recycling.
- 2.3.7 The operator shall ensure that where waste produced by the activities is sent to a relevant waste operation, that operation is provided with the following information, prior to the receipt of the waste:
  - (a) the nature of the process producing the waste;
  - (b) the composition of the waste;
  - (c) the handling requirements of the waste;
  - (d) the hazardous property associated with the waste, if applicable; and
  - (e) the waste code of the waste.
- 2.3.8 The operator shall ensure that where waste produced by the activities is sent to a landfill site, it meets the waste acceptance criteria for that landfill.
- 2.3.9 Waste shall not be charged if:
  - (a) the combustion chamber temperature is below 850 °C,
  - (b) any continuous emission limit value in schedule 3 table S3.1(a) is exceeded; or
  - (c) any continuous emission limit value in schedule 3 table S3.1 is exceeded, other than during abnormal operation; or
  - (d) continuous emission monitors to demonstrate compliance with any continuous emission limit value in schedule 3 table S3.1 are unavailable other than during abnormal operation; or
  - (e) there is a stoppage, disturbance or failure of the activated carbon abatement system, other than during abnormal operation.
  - (f) continuous emission monitors to demonstrate compliance with the emission limit values for particulates, TOC or CO in schedule 3 are unavailable unless alternative techniques, as agreed in writing with the Environment Agency, are used to demonstrate compliance with those emission limit values.
- 2.3.10 The operator shall record the beginning and end of each period of "abnormal operation".
- 2.3.11 During a period of "abnormal operation", the operator shall restore normal operation of the failed equipment or replace the failed equipment as soon as possible.
- 2.3.12 The operator shall interpret the start of the period of "abnormal operation" as the earliest of the following:
  - (a) a technically unavoidable stoppage, disturbance, or failure of continuous emission monitors.
  - (b) a technically unavoidable stoppage, disturbance, or failure of the activated carbon abatement system
  - (c) Any other technically unavoidable stoppage, disturbance, or failure of the plant which is causing or could lead to an exceedance of an emission limit value in table S3.1.
- 2.3.13 The operator shall interpret the end of the period of "abnormal operation" as the earliest of the following:
  - (a) when the failed equipment is repaired and brought back into normal operation;

- (b) when the operator initiates a shut down of the waste combustion activity, as described in the application or as agreed in writing with the Environment Agency;
- (c) The failed equipment has not been repaired and brought back into normal operation and a single period of abnormal operation reaches a duration of 4 hours after the start of abnormal operation on an incineration line
- (d) Abnormal operation occurs on an incineration line and the cumulative duration of abnormal operation periods over 1 calendar year has reached 60 hours on that incineration line;
- 2.3.14 The operator shall have at least one auxiliary burner in each line which shall be operated at start up, shut down and as required during operation to ensure that the operating temperature specified in condition 2.3.9 is maintained as long as incompletely burned waste is present in the combustion chamber. Unless the temperature specified in condition 2.3.9 is maintained in the combustion chamber, such burner(s) shall be fed only with fuels which result in emissions no higher than those arising from the use of gas oil, liquefied gas or natural gas.
- 2.3.15 Bottom ash and APC residues shall not be mixed.

#### 2.4 Improvement programme

- 2.4.1 The operator shall complete the improvements specified in schedule 1 table S1.3 by the date specified in that table unless otherwise agreed in writing by the Environment Agency.
- 2.4.2 Except in the case of an improvement which consists only of a submission to the Environment Agency, the operator shall notify the Environment Agency within 14 days of completion of each improvement.

#### 3 Emissions and monitoring

#### 3.1 Emissions to water, air or land

- 3.1.1 There shall be no point source emissions to water, air or land except from the sources and emission points listed in schedule 3 tables S3.1 and S3.2.
- 3.1.2 The limits given in schedule 3, subject to condition 3.2.1, shall not be exceeded.
- 3.1.3 Wastes produced at the site shall, as a minimum, be sampled and analysed in accordance with schedule 3 table S3.4. Additional samples shall be taken and tested and appropriate action taken, whenever:
  - (a) disposal or recovery routes change; or
  - (b) it is suspected that the nature or composition of the waste has changed such that the route currently selected may no longer be appropriate.

## 3.2 Emissions limits and monitoring for emission to air for incineration plant

- 3.2.1 The limits for emissions to air apply as follows:
  - (a) The limits in table S3.1 shall not be exceeded except during periods of abnormal operation.
  - (b) The limits in table S3.1 (a) shall not be exceeded.
- 3.2.2 Where Continuous Emission Monitors are installed to comply with the monitoring requirements in schedule 3 table S3.1 and S3.1(a); the Continuous Emission Monitors shall be used such that:

(a) the values of the 95% confidence intervals of a single measured result at the daily emission limit value shall not exceed the following percentages of the emission limit values:

•	Carbon monoxide	10%
•	Sulphur dioxide	20%
•	Oxides of nitrogen (NO & NO <sub>2</sub> expressed as NO <sub>2</sub> )	20%
•	Particulate matter	30%
•	Total organic carbon (TOC)	30%
•	Hydrogen chloride	40%
•	Ammonia	40%

- (b) valid half-hourly average values or 10-minute averages shall be determined within the effective operating time (excluding the start-up and shut-down periods) from the measured values after having subtracted the value of the confidence intervals in condition 3.2.2 (a).
- (c) where it is necessary to calibrate or maintain the monitor and this means that data are not available for a complete half-hour or 10 minute period, the half-hourly average or 10-minute average shall in any case be considered valid if measurements are available for a minimum of 20 minutes or 7 minutes during the half-hour or 10-minute period respectively. The number of half-hourly or 10-minute averages so validated shall not exceed 5 or 15 respectively per day;
- (d) daily average values shall be calculated as follows:
  - (i) the average of valid half hourly averages or 10 minute averages over a calendar day excluding half hourly averages or 10 minute averages during periods of abnormal operation. The daily average value shall be considered valid if no more than five half-hourly average or fifteen 10-minute average values in any day have been determined not to be valid;
- (e) no more than ten daily average values per year shall be determined not to be valid.

#### 3.3 Emissions of substances not controlled by emission limits

- 3.3.1 Emissions of substances not controlled by emission limits (excluding odour) shall not cause pollution. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved emissions management plan, have been taken to prevent or where that is not practicable, to minimise, those emissions.
- 3.3.2 The operator shall:
  - (a) if notified by the Environment Agency that the activities are giving rise to pollution, submit to the Environment Agency for approval within the period specified, an emissions management plan which identifies and minimises the risks of pollution from emissions of substances not controlled by emission limits;
  - (b) implement the approved emissions management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.
- 3.3.3 All liquids in containers, whose emission to water or land could cause pollution, shall be provided with secondary containment, unless the operator has used other appropriate measures to prevent or where that is not practicable, to minimise, leakage and spillage from the primary container.
- 3.3.4 Periodic monitoring shall be carried out at least once every 5 years for groundwater and 10 years for soil, unless such monitoring is based on a systematic appraisal of the risk of contamination.

#### 3.4 Odour

- 3.4.1 Emissions from the activities shall be free from odour at levels likely to cause pollution outside the site, as perceived by an authorised officer of the Environment Agency, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved odour management plan, to prevent or where that is not practicable to minimise the odour.
- 3.4.2 The operator shall:
  - (a) if notified by the Environment Agency that the activities are giving rise to pollution outside the site due to odour, submit to the Environment Agency for approval within the period specified, an odour management plan which identifies and minimises the risks of pollution from odour;
  - (b) implement the approved odour management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

#### 3.5 Noise and vibration

- 3.5.1 Emissions from the activities shall be free from noise and vibration at levels likely to cause pollution outside the site, as perceived by an authorised officer of the Environment Agency, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved noise and vibration management plan to prevent or where that is not practicable to minimise the noise and vibration.
- 3.5.2 The operator shall:
  - (a) if notified by the Environment Agency that the activities are giving rise to pollution outside the site due to noise and vibration, submit to the Environment Agency for approval within the period specified, a noise and vibration management plan which identifies and minimises the risks of pollution from noise and vibration;
  - (b) implement the approved noise and vibration management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

#### 3.6 Monitoring

- 3.6.1 The operator shall, unless otherwise agreed in writing by the Environment Agency, undertake the monitoring specified in the following tables in schedule 3 to this permit:
  - (a) point source emissions specified in tables S3.1, S3.1(a) and S3.2;
  - (b) process monitoring specified in table S3.3; and
  - (c) residue quality in table S3.4.
- 3.6.2 The operator shall maintain records of all monitoring required by this permit including records of the taking and analysis of samples, instrument measurements (periodic and continual), calibrations, examinations, tests and surveys and any assessment or evaluation made on the basis of such data.
- 3.6.3 Monitoring equipment, techniques, personnel and organisations employed for the emissions monitoring programme and the environmental or other monitoring specified in condition 3.6.1 shall have either MCERTS certification or MCERTS accreditation (as appropriate) unless otherwise agreed in writing by the Environment Agency. Newly installed CEMs, or CEMs replacing existing CEMs, shall have MCERTS certification and unless otherwise agreed in writing by the Environment Agency have an MCERTS certified range which is not greater than 1.5 times the daily emission limit value (ELV) specified in schedule 3 table S3.1. The CEM shall also be able to measure instantaneous values over the ranges which are to be expected during all operating conditions. If it is necessary to use more than one range setting of the CEM to achieve this requirement, the CEM shall

- be verified for monitoring supplementary, higher ranges. Newly installed Data handling and acquisition systems (DAHS), or DAHS replacing existing DAHS, shall have MCERTS certification.
- 3.6.4 Permanent means of access shall be provided to enable sampling/monitoring to be carried out in relation to the emission points specified in schedule 3 tables S3.1, S3.1(a) and S3.2 unless otherwise agreed in writing by the Environment Agency.

#### 3.7 Pests

- 3.7.1 The activities shall not give rise to the presence of pests which are likely to cause pollution, hazard or annoyance outside the boundary of the site. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved pests management plan, have been taken to prevent or where that is not practicable, to minimise the presence of pests on the site.
- 3.7.2 The operator shall:
  - (a) if notified by the Environment Agency, submit to the Environment Agency for approval within the period specified, a pests management plan which identifies and minimises risks of pollution from pests;
  - (b) implement the pests management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

#### 3.8 Fire prevention

- 3.8.1 The operator shall take all appropriate measures to prevent fires on site and minimise the risk of pollution from them including, but not limited to, those specified in any approved fire prevention plan.
- 3.8.2 The operator shall:
  - (a) if notified by the Environment Agency that the activities are giving rise to a risk of fire, submit to the Environment Agency for approval within the period specified, a fire prevention plan which prevents fires and minimises the risk of pollution from fires;
  - (b) implement the fire prevention plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

#### 4 Information

#### 4.1 Records

- 4.1.1 All records required to be made by this permit shall:
  - (a) be legible;
  - (b) be made as soon as reasonably practicable;
  - (c) if amended, be amended in such a way that the original and any subsequent amendments remain legible, or are capable of retrieval; and
  - (d) be retained, unless otherwise agreed in writing by the Environment Agency, for at least 6 years from the date when the records were made, or in the case of the following records until permit surrender:
    - (i) off-site environmental effects; and
    - (ii) matters which affect the condition of the land and groundwater.

4.1.2 The operator shall keep on site all records, plans and the management system required to be maintained by this permit, unless otherwise agreed in writing by the Environment Agency.

#### 4.2 Reporting

- 4.2.1 The operator shall send all reports and notifications required by the permit to the Environment Agency using the contact details supplied in writing by the Environment Agency.
- 4.2.2 A report or reports on the performance of the activities over the previous year shall be submitted to the Environment Agency by 31 January (or other date agreed in writing by the Environment Agency) each year using the annual report form specified in schedule 4, table S4.4 or otherwise in a format agreed with the Environment Agency. The report(s) shall include as a minimum:
  - (a) a review of the results of the monitoring and assessment carried out in accordance with the permit including an interpretive review of that data;
  - (b) the annual production /treatment data set out in schedule 4 table S4.2;
  - (c) the performance parameters set out in schedule 4 table S4.3
  - (d) the functioning and monitoring of the incineration plant in a format agreed with the Environment Agency. The report shall, as a minimum requirement (as required by Chapter IV of the Industrial Emissions Directive) give an account of the running of the process and the emissions into air and water compared with the emission standards in the IED.
- 4.2.3 Within 28 days of the end of the reporting period the operator shall, unless otherwise agreed in writing by the Environment Agency, submit reports of the monitoring and assessment carried out in accordance with the conditions of this permit, as follows:
  - (a) in respect of the parameters and emission points specified in schedule 4 table S4.1;
  - (b) for the reporting periods specified in schedule 4 table S4.1 and using the forms specified in schedule 4 table S4.4; and
  - (c) giving the information from such results and assessments as may be required by the forms specified in those tables.
- 4.2.4 The operator shall, unless notice under this condition has been served within the preceding four years, submit to the Environment Agency, within six months of receipt of a written notice, a report assessing whether there are other appropriate measures that could be taken to prevent, or where that is not practicable, to minimise pollution.
- 4.2.5 Within 1 month of the end of each quarter, the operator shall submit to the Environment Agency using the form made available for the purpose, the information specified on the form relating to the site and the waste accepted and removed from it during the previous quarter.

#### 4.3 Notifications

- 4.3.1 In the event:
  - (a) that the operation of the activities gives rise to an incident or accident which significantly affects or may significantly affect the environment, the operator must immediately:
    - (i) inform the Environment Agency,
    - (ii) take the measures necessary to limit the environmental consequences of such an incident or accident, and
    - (iii) take the measures necessary to prevent further possible incidents or accidents;

- (b) of a breach of any permit condition the operator must immediately:
  - (i) inform the Environment Agency, and
  - (ii) take the measures necessary to ensure that compliance is restored within the shortest possible time;
- (c) of a breach of permit condition which poses an immediate danger to human health or threatens to cause an immediate significant adverse effect on the environment, the operator must immediately suspend the operation of the activities or the relevant part of it until compliance with the permit conditions has been restored.
- 4.3.2 Any information provided under condition 4.3.1 shall be confirmed by sending the information listed in schedule 5 to this permit within the time period specified in that schedule.
- 4.3.3 Where the Environment Agency has requested in writing that it shall be notified when the operator is to undertake monitoring and/or spot sampling, the operator shall inform the Environment Agency when the relevant monitoring and/or spot sampling is to take place. The operator shall provide this information to the Environment Agency at least 14 days before the date the monitoring is to be undertaken.
- 4.3.4 The Environment Agency shall be notified within 14 days of the occurrence of the following matters, except where such disclosure is prohibited by Stock Exchange rules:

Where the operator is a registered company:

- (a) any change in the operator's trading name, registered name or registered office address; and
- (b) any steps taken with a view to the operator going into administration, entering into a company voluntary arrangement or being wound up.

Where the operator is a corporate body other than a registered company:

- (a) any change in the operator's name or address; and
- (b) any steps taken with a view to the dissolution of the operator.
- 4.3.5 Where the operator proposes to make a change in the nature or functioning, or an extension of the activities, which may have consequences for the environment and the change is not otherwise the subject of an application for approval under the Regulations or this permit:
  - (a) the Environment Agency shall be notified at least 14 days before making the change; and
  - (b) the notification shall contain a description of the proposed change in operation.
- 4.3.6 The Environment Agency shall be given at least 14 days notice before implementation of any part of the site closure plan.

#### 4.4 Interpretation

- 4.4.1 In this permit the expressions listed in schedule 6 shall have the meaning given in that schedule.
- 4.4.2 In this permit references to reports and notifications mean written reports and notifications, except where reference is made to notification being made "immediately" or "without delay" in which case it may be provided by telephone.

## **Schedule 1 – Operations**

Table S1.1 activities			
Activity reference	Activity listed in Schedule 1 of the EP Regulations	Description of specified activity	Limits of specified activity
AR1	S5.1 A1 (b)	The incineration of non-hazardous waste in a waste incineration plant with a capacity of 3 tonnes per hour or more.	From receipt of waste to emission of exhaust gas and disposal of waste arising.  Waste types and quantities as specified in Table S2.2 and S2.3 of this permit.
	Directly Associated Activities		
AR2	Electricity Generation and/or supply of heat	Generation of electrical power and supply of heat using a steam turbine from energy recovered from the flue gases.	Supply of electricity to the national grid and for use within the installation.  Supply of heat.
AR3	Back up electrical generator	For providing emergency electrical power to the plant in the event of supply interruption.	Emergency use to a maximum of 500 hours operation per year.  Maximum of 50 hours testing per year.

Table S1.2 Operating techniques		
Description	Parts	Date Received
Application EPR/GP3334CX/A001	Response to question 3 of application form B3; Sections 4, 6.7, 7,3, 8, 12.3.1, 12.5 and 13.5 of volume 2.	02/08/2012
Response to Schedule 5 Notice dated 19/11/2012	Response to questions 3 and 17	07/01/2013
Additional information	Information about operation and maintenance of carbon filter	15/02/2013
Response to improvement condition IC1	Operating techniques as set out in improvement condition response as approved by the Environment Agency	Date IC1 response was received

	Table S1.3 Improvement programme requirements		
Reference	Requirement	Date	
IC1	The operator shall submit a report to the Environment Agency for approval (using the form provided by the Environment Agency) that addresses compliance with each BAT conclusion. The report shall include:	3 months from issue of variation notice	
	i. If any BAT conclusion is not relevant explain why		
	ii. Whether and how the installation complies with the standards in set out in each BAT conclusion		
	iii. If the installation does not currently comply with a standard set in a BAT conclusion describe how and when the installation will comply with that standard.		
	iv. If the installation will continue operating in a manner which would not comply with a BAT Conclusion, after 03/12/2023 the operator shall submit to the Environment Agency:		
	a justification for being allowed to do so		
	<ul> <li>a description of alternative measures to be adopted that will provide equivalent environmental protection</li> </ul>		
	The operator shall obtain the Environment Agency's written approval to the report.		
IC2	The operator shall submit a report to the Environment Agency on whether waste feed to the plant can be proven to have a low and stable mercury content. The report shall have regard to BAT 4 of the BAT conclusions, be based on historic mercury emissions monitoring data and have regard to the Environment Agency Mercury Monitoring Protocol.	30/09/23	
IC3	The operator shall submit a report to the Environment Agency on whether dioxin emissions to air are stable. The report shall have regard to BAT 4 of the BAT conclusions, be based on historic dioxin emissions monitoring data and have regard to the Environment Agency Dioxins Monitoring Protocol.	30/09/23	
IC4	The operator shall perform a study to determine the extent to which the operation of the current systems in place at the plant to minimise NOx emissions can be further optimised such that emissions are reduced as far as possible below 180 mg/Nm³ as a daily average, without significantly increasing emissions of other pollutants or having a significant negative effect on plant operation, reliability or bottom ash quality. The study shall be based on the results of trials carried out at the installation and shall have regard to the recommendations for test conditions set out in Section 5.4.3 of report titled 'Establishing factors that influence NOx reduction at waste incineration plant to levels below the upper end of the BAT-AELs' (dated 14/01/2022), or other methodology agreed in writing with the Environment Agency. A written report of the study shall be submitted to the Environment Agency which shall include but not necessarily be limited to the following:  • A brief description of the currently installed measures at the installation to minimise NOx emissions, including details of how the reagent dosing system responds to emissions monitoring data and historic data which illustrates the current achievable level of daily NOx emissions.	12 months from issue of variation notice	

Reference	Requirement	Date
Reference	The results of trials conducted to further reduce daily average NOx emissions using currently installed measures, including:  a description of the parameters that were varied during the trial e.g. ammonia or urea feed rates, physical form of urea injected, air flows, and the range over which they were varied  the levels of NOx achieved and associated levels of ammonia and nitrous oxide emissions and reagent consumption  observed effects and predicted long-term impacts on plant operation, reliability and maintenance regime  any changes to the composition of the bottom ash and boiler ash and the implications of those changes for the ability to process and use the ash, as well as for the pollution potential of the ash both during processing and its subsequent use as a secondary aggregate  any other relevant cross-media effects  The report shall also include a description of the extent to which current systems in place at the plant to minimise NOx emissions can be optimised on a permanent basis, including justification and an implementation plan	
IC5	<ul> <li>where relevant.</li> <li>Where the response to IC1 shows that the energy efficiency will be below the bottom of the BAT AEEL range specified in BAT 20 after 02/12/2023 the operator shall carry out an assessment of the opportunities to increase the energy efficiency of the installation.</li> <li>The assessment shall include but not necessarily be limited to: <ul> <li>Improvements that could be made to the furnace (including control systems) in order to increase the amount of thermal energy produced per unit of thermal energy in the waste.</li> <li>Improvements that could be made to the steam system and related components to allow a greater quantity of electricity to be generated per unit of thermal energy in the steam.</li> <li>Improvements in the heat and electrical efficiency of the plant's ancillary systems that could be made in order to reduce the parasitic heat and electrical loads of the plant.</li> <li>Where relevant, an implementation plan for the improvements identified, including the anticipated increase in the gross and/or net electrical efficiency of the plant which would be achieved.</li> </ul> </li> <li>A written copy of the assessment shall be submitted to the Environment Agency.</li> </ul>	12 months from issue of variation notice

## Schedule 2 – Waste types, raw materials and fuels

Table S2.1 Raw materials and fuels		
Raw materials and fuel description Specification		
Fuel Oil	< 0.1% sulphur content	

Table S2.2 Permitt	ted waste types and quantities for pre-treatment and then incineration
Maximum quantity	214,000 tonnes per year for pre-treatment
Waste code	Description
15	Waste packaging; absorbents, wiping cloths, filter materials and protective clothing not otherwise specified
15 01	packaging (including separately collected municipal packaging waste)
15 01 01	paper and cardboard packaging
15 01 06	mixed packaging
15 01 09	textile packaging
15 02	absorbents, filter materials, wiping cloths and protective clothing
15 02 03	absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02
16	Wastes not otherwise specified in the list
16 03	off-specification batches and unused products
16 03 06	organic wastes other than those mentioned in 16 03 05
19	Wastes from waste management facilities, off-site waste water treatment plants and the preparation of water intended for human consumption and water for industrial use
19 12	wastes from the mechanical treatment of waste (for example sorting, crushing, compacting, pelletising) not otherwise specified
19 12 01	paper and cardboard
19 12 07	wood other than that mentioned in 19 12 06
19 12 12	other wastes (including mixtures of materials) from mechanical treatment of wastes other than those mentioned in 19 12 11
20	Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions
20 01	separately collected fractions (except 15 01)
20 01 38	wood other than that mentioned in 20 01 37
20 03	other municipal wastes
20 03 01	mixed municipal waste
20 03 02	waste from markets
20 03 07	bulky waste

Maximum quantity	ted waste types and quantities for incineration plant
waxiiiiuiii quantity	190,000 tonnes per year. This quantity includes wastes from table S2.2 after the pre-
<b>NA</b>	treatment
Waste code	Description
02	Wastes from agriculture, horticulture, aquaculture, forestry, hunting and fishing food preparation and processing
02 02	wastes from the preparation and processing of meat, fish and other foods of animal origin
02 02 02	animal-tissue waste
02 02 03	materials unsuitable for consumption or processing
16	Wastes not otherwise specified in the list
16 02	wastes from electrical and electronic equipment
16 02 16	components removed from discarded equipment other than those mentioned in 16 02 15
16 03	off-specification batches and unused products
16 03 06	organic wastes other than those mentioned in 16 03 05
18	Wastes from human or animal health care and/or related research (except kitchen and restaurant wastes not arising from immediate health care)
18 01	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 04	wastes whose collection and disposal is not subject to special requirements in order to prevent infection (for example dressings, plaster casts, linen, disposable clothing, diapers)
19	Wastes from waste management facilities, off-site waste water treatment plants and the preparation of water intended for human consumption and water for industrial use
19 12	wastes from the mechanical treatment of waste (for example sorting, crushing, compacting, pelletising) not otherwise specified
19 12 01	paper and cardboard
19 12 07	wood other than that mentioned in 19 12 06
19 12 08	textiles
19 12 10	combustible waste (refuse derived fuel)
19 12 12	other wastes (including mixtures of materials) from mechanical treatment of wastes other than those mentioned in 19 12 11
20	Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions
20 01	separately collected fractions (except 15 01)
20 01 01	paper and cardboard
20 01 08	biodegradable kitchen and canteen waste
20 01 10	clothes
20 01 11	textiles
20 01 38	wood other than that mentioned in 20 01 37
20 01 39	plastics
	other fractions not otherwise specified (comprising only of non-clinical human and
20 01 99	animal offensive/hygiene waste (not arising from healthcare and/or related research i.e. not including waste from natal care, diagnosis, treatment or prevention of disease) which is not subject to special requirements in order to prevent infection)
20 01 99 20 02	i.e. not including waste from natal care, diagnosis, treatment or prevention of disease)
	i.e. not including waste from natal care, diagnosis, treatment or prevention of disease) which is not subject to special requirements in order to prevent infection)
20 02	i.e. not including waste from natal care, diagnosis, treatment or prevention of disease) which is not subject to special requirements in order to prevent infection)  garden and park wastes (including cemetery waste)
<b>20 02</b> 20 02 01	i.e. not including waste from natal care, diagnosis, treatment or prevention of disease which is not subject to special requirements in order to prevent infection)  garden and park wastes (including cemetery waste)  biodegradable waste

Table S2.3 Permitt	Table S2.3 Permitted waste types and quantities for incineration plant							
Maximum quantity 190,000 tonnes per year. This quantity includes wastes from table S2.2 after the pre treatment								
Waste code	Description							
20 03 03	street-cleaning residues							
20 03 07	bulky waste							

### Schedule 3 – Emissions and monitoring

Table S3.1 I	Point source emissions t	o air – emission lim	its and monitoring	requirements.		
Emission point ref. & location (as shown on site plan in schedule 7)	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
A1	Particulate matter	Incineration exhaust gases	30 mg/m <sup>3</sup>	½-hr average	Continuous	EN 14181
A1	Particulate matter	Incineration exhaust gases	10 mg/m <sup>3</sup> until 02/12/2023	daily average	Continuous	EN 14181
			5 mg/m <sup>3</sup> from 03/12/2023			
A1	Total Organic Carbon (TOC)	Incineration exhaust gases	20 mg/m <sup>3</sup>	½-hr average	Continuous	EN 14181
A1	Total Organic Carbon (TOC)		10 mg/m <sup>3</sup>	daily average	Continuous	EN 14181
A1	Hydrogen chloride	Incineration	60 mg/m <sup>3</sup>	½-hr average	Continuous	EN 14181
A1	Hydrogen chloride	exhaust gases	10 mg/m <sup>3</sup> until 02/12/2023	daily average	Continuous	EN 14181
			8 mg/m <sup>3</sup> from 03/12/2023			

Emission point ref. & location (as shown on site plan	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
in schedule 7)						
A1	Hydrogen fluoride	Incineration exhaust gases	2 mg/m <sup>3</sup> until 02/12/2023	Average of three consecutive measurements of	Bi-annually	CEN TS 17340 [BS ISO 15713 can be used until 01/03/22]
			1 mg/m <sup>3</sup> from 03/12/2023	at least 30 minutes each		
A1	Carbon monoxide	Incineration exhaust gases	150 mg/m <sup>3</sup>	95% of all 10- minute averages in any 24-hour period	Continuous	EN 14181
A1	Carbon monoxide		50 mg/m <sup>3</sup>	daily average	Continuous	EN 14181
A1	Sulphur dioxide	Incineration	200 mg/m <sup>3</sup>	½-hr average	Continuous	EN 14181
A1	Sulphur dioxide	exhaust gases	50 mg/m <sup>3</sup> until 02/12/2023	daily average	Continuous	EN 14181
			40 mg/m <sup>3</sup> from 03/12/2023			
A1	Oxides of nitrogen (NO and NO <sub>2</sub> expressed as NO <sub>2</sub> )	Incineration exhaust gases	400 mg/m <sup>3</sup>	½-hr average	Continuous	EN 14181
A1	Oxides of nitrogen (NO and NO <sub>2</sub> expressed as NO <sub>2</sub> )		200 mg/m <sup>3</sup> until 02/12/2023	daily average	Continuous	EN 14181

Emission point ref. & location (as shown on site plan in schedule 7)	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
			180 mg/m <sup>3</sup> from 03/12/2023			
A1	Cadmium & thallium and their compounds (total)		0.05 mg/m³ until 02/12/2023	Average of three consecutive	Bi-annually	BS EN 14385
			0.02 mg/m3 from 03/12/2023	measurements of at least 30 minutes each		
A1	Mercury and its compounds	Incineration exhaust gases	0.05 mg/m <sup>3</sup> until 02/12/2023	Average of three consecutive measurements of at least 30 minutes each	Bi-annually until 02/12/2023	BS EN 13211

Emission point ref. & location (as shown on site plan in schedule	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
7) A1	Mercury and its compounds	Incineration exhaust gases	0.02 mg/m³ from 03/12/2023  Limit does not apply if continuous monitoring has been specified in writing by the Environment Agency	Average of three consecutive measurements of at least 30 minutes each	Bi-annually from 03/12/2023  Not required if continuous monitoring has been specified in writing by the Environment Agency	BS EN 13211
A1	Mercury and its compounds	Incineration exhaust gases	0.02 mg/m <sup>3</sup> from 03/12/2023	Daily average	Continuous from 03/12/2023  Not required unless continuous monitoring has been specified in writing by the Environment Agency in line with sampling protocol	EN 14181

Emission point ref. & location (as shown on site plan in schedule	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
A1	Sb, As, Pb, Cr, Co, Cu, Mn, Ni and V and their compounds (total)	Incineration exhaust gases	0.5 mg/m <sup>3</sup> until 02/12/2023 0.3 mg/m <sup>3</sup> from 03/12/2023	Average of three consecutive measurements of at least 30 minutes each	Bi-annually from 03/12/2023	BS EN 14385
A1	Exhaust gas temperature	Incineration exhaust gases	No limit set	-	Continuous	Traceable to national standards
A1	Exhaust gas pressure	Incineration exhaust gases	No limit set	-	Continuous	Traceable to national standards
A1	Exhaust gas flow	Incineration exhaust gases	No limit set	-	Continuous from 01/01/2023	BS EN 16911-2
A1	Exhaust gas oxygen content	Incineration exhaust gases	No limit set	-	Continuous	EN 14181
A1	Exhaust gas water vapour content	Incineration exhaust gases	No limit set	-	Continuous	EN 14181
A1 .	Ammonia (NH <sub>3</sub> )	Incineration exhaust gases	No limit set until 02/12/2023	½-hr average and daily average	Continuous until 02/12/2023	EN 14181
			15 mg/m <sup>3</sup> from 03/12/2023	daily average	Continuous from 03/12/2023	EN 14181

Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
(as shown on site plan in schedule 7)						
A1	Nitrous oxide (N2O)	Incineration exhaust gases	No limit set	periodic over minimum 1-hour period until 01/01/2023	Bi-annually until 01/01/2023	EN ISO 21258
A1	Nitrous oxide (N <sub>2</sub> O)		No limit set	½-hr average and daily average from 01/01/2023	Continuous from 01/01/2023	EN 14181
A1	Carbon dioxide	Incineration exhaust gases	No limit set	Continuous	Continuous from 01/01/2023	EN 14181
A1	Dioxins / furans (I-TEQ)	Incineration exhaust gases	0.1 ng/m <sup>3</sup> until 02/12/2023	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually until 02/12/2023	BS EN 1948 Parts 1, 2 and 3

Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
(as shown on site plan in schedule 7)						
	Dioxins / furans (I-TEQ)	rans (I-TEQ) Incineration exhaust gases	0.06 ng/m <sup>3</sup>	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually from 03/12/2023	EN 1948 Parts 1, 2 and 3
			or  0.08 ng/m³ if long term limit is specified by the Environment Agency in line with sampling protocol from 03/12/2023	value over sampling period of 2 to 4 weeks for long term sampling	or long term sampling if specified by the Environment Agency in line with sampling protocol from 03/12/2023	or  CEN TS 1948-5 if specified by the Environment Agency in line with sampling protocol

Emission point ref. & location (as shown on site plan in schedule	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
<b>7)</b> A1	Dioxin-like PCBs (WHO- TEQ Humans / Mammals, Fish, Birds)	Incineration exhaust gases	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually;	EN 1948 Parts 1, 2 and 4
				or	or	
				value over sampling period of 2 to 4 weeks for long term sampling	long term sampling if specified by the Environment Agency in line with sampling protocol 03/12/2023.  No monitoring is required if emissions have been shown to be below 0.01 ng/m³ as agreed with the Environment Agency.	or  CEN TS 1948-5 if specified by the Environment Agency in line with sampling protocol
A1	Dioxins / furans (WHO-TEQ Humans / Mammals, Fish, Birds)	Incineration exhaust gases	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	BS EN 1948 Parts 1, 2 and 3

Emission point ref. & location (as shown on site plan in schedule 7)	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
A1	Polybrominated dibenzo- dioxins and furans	Incineration exhaust gases	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually from 01/01/2023 Not required unless wastes containing brominated flame retardants are burned	Method based on procedural requirements of EN 1948
A1	Specific individual polycyclic aromatic hydrocarbons (PAHs), as specified in Schedule 6	Incineration exhaust gases	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Annually	BS ISO 11338 Parts 1 and 2.
A5	Carbon monoxide	Emergency diesel generator	No limit set	In line with web guide 'Monitoring stack emissions: low risk MCPs and specified generators' Published 16 February 2021 (formerly known as TGN M5)	Every 1500 hours of operation or once every five years (whichever comes first) from 01/01/2030	In line with web guide 'Monitoring stack emissions: low risk MCPs and specified generators' Published 16 February 2021 (formerly known as TGN M5)
A7	No parameters set	Activated carbon filters	No limit set	-	-	-

Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
(as shown on site plan in schedule 7)						
A8-A10	No parameters set	Boiler vent and relief valves	No limit set	-	-	-

Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
A1	Particulate matter	Incineration exhaust gases	150 mg/m <sup>3</sup>	½-hr average	Continuous	en 14181  or  alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor
A1	Total Organic Carbon (TOC)		20 mg/m <sup>3</sup>	½-hr average	Continuous	en 14181  or alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor
A1	Carbon monoxide		150 mg/m <sup>3</sup>	95% of all 10-minute averages in any 24- hour period	Continuous	en 14181  or alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor

Table S3.2 Point source emissions to sewer, effluent treatment plant or other transfers off-site-emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (incl. Unit)	Reference period	Monitoring frequency	Monitoring standard or method
W2 (shown on site plan in Schedule 7 of this permit)	Batch discharge of waste water via settlement and pH treatment equipment	No parameters set	No limit set	-	-	-
W3, W4, W5 (shown on site plan in Schedule 7 of this permit)	Uncontaminated surface water	No parameters set	No limit set	-	-	-

Table S3.3 Process monitoring requirements						
Emission point reference or source or description of point of measurement	Parameter	Monitoring frequency	Monitoring standard or method	Other specifications		
As identified in the Application	Wind Speed and Direction	Continuous	Anemometer			
Location close to the Combustion Chamber inner wall or as identified and justified in Application.	Temperature (°C)	Continuous	Traceable to national standards	As agreed in writing with the Agency.		
Incineration plant	Gross electrical efficiency	within 6 months of any modification that significantly affects energy efficiency	Performance test at full load or other method as agreed in writing with the Environment Agency			

Table S3.4 Residue quality					
Emission point reference or source or description of point of measurement	Parameter	Limit	Monitoring frequency	Monitoring standard or method *	Other specifications
Bottom Ash	TOC	3%	Quarterly	EN 14899 and either EN 13137 or EN 15936	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'
Bottom Ash	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	-	Quarterly	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'	
Bottom Ash	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	-	Quarterly	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'	
APC Residues	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	-	Quarterly	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'	
APC Residues	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	-	Before use of a new disposal or recycling route	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'	

<sup>\*</sup> Or other equivalent standard as agreed in writing with the Environment Agency.

## Schedule 4 – Reporting

Parameters, for which reports shall be made, in accordance with conditions of this permit, are listed below.

Table S4.1 Reporting of monitoring data					
Parameter	Emission or monitoring point/reference	Reporting period	Period begins		
Emissions to air Parameters as required by condition 3.6.1	A1	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct		
TOC Parameters as required by condition 3.6.1	Bottom Ash	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct		
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1	Bottom Ash	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct		
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions  Parameters as required by condition 3.6.1	Bottom Ash	Before use of a new disposal or recycling route			
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1	APC Residues	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct		
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions  Parameters as required by condition 3.6.1	APC Residues	Before use of a new disposal or recycling route			

Table S4.2: Annual production/treatment				
Parameter Units				
Total Waste Incinerated	tonnes			
Electrical energy produced	MWh			
Thermal energy exported	MWh			

Table S4.2: Annual production/treatment				
Parameter	Units			
Electrical energy exported	MWh			
Electrical energy used on installation	MWh			
Waste heat utilised by the installation	MWh			

Table S4.3 Performance parameters					
Parameter	Frequency of assessment	Units			
Annual Report as required by condition 4.2.2	Annually	-			
Electrical energy exported, imported and used at the installation	Annually	KWh / tonne of waste incinerated			
Fuel oil consumption	Annually	Kg / tonne of waste incinerated			
Bottom Ash residue	Annually	Route, tonnes and tonnes / tonne of waste incinerated			
APC residue	Annually	Route, tonnes and tonnes / tonne of waste incinerated			
Urea consumption	Annually	Kg / tonne of waste incinerated			
Activated Carbon consumption	Annually	Kg / tonne of waste incinerated			
Lime consumption	Annually	Kg / tonne of waste incinerated			
Water consumption	Annually	Kg / tonne of waste incinerated			
Periods of abnormal operation	Annually	No of occasions and cumulative hours for current calendar year for each line.			

Table S4.4 Reporting forms						
Media/parameter	Reporting format	Date of form				
Annual report required by condition 4.2.2	Annual performance report template	15/03/22				
Emissions to air until 02/12/2023	Form air 1-7 or other forms as agreed in writing by the Environment Agency	01/07/13				
Emissions to air from 03/12/2023	Forms air 1-9 or other forms as agreed in writing by the Environment Agency	15/03/22				
Residue quality	Form residue 1 and 2 or other forms as agreed in writing by the Environment Agency	15/03/22				

#### Schedule 5 - Notification

These pages outline the information that the operator must provide.

Units of measurement used in information supplied under Part A and B requirements shall be appropriate to the circumstances of the emission. Where appropriate, a comparison should be made of actual emissions and authorised emission limits.

If any information is considered commercially confidential, it should be separated from non-confidential information, supplied on a separate sheet and accompanied by an application for commercial confidentiality under the provisions of the EP Regulations.

#### Part A

any malfunction, breakdown or failure of equipment or techniques, nce not controlled by an emission limit which has caused, is pollution
detection
the breach of a limit
detection unless otherwise specified below

(b) Notification requirements for	he breach of a li	mit	
To be notified within 24 hours of	detection unless	otherwise specified be	low
Measures taken, or intended to be taken, to stop the emission			
Time periods for notification follo	wing detection o	of a breach of a limit	
Parameter	3		Notification period
			•
(c) Notification requirements for t	he breach of per	rmit conditions not relat	ed to limits
To be notified within 24 hours of det	ection		
Condition breached			
Date, time and duration of breach			
Details of the permit breach i.e. what happened including impacts observed.			
Measures taken, or intended to be taken, to restore permit compliance.			
(d) Notification requirements for		any significant adverse	environmental effect
To be notified within 24 hours of	detection		
Description of where the effect on the environment was detected			
Substances(s) detected			
Concentrations of substances detected			
Date of monitoring/sampling			
Part B – to be submit		n as practicabl	е
Any more accurate information on the notification under Part A.	ne matters for		

Measures taken, or intended to be taken, to prevent a recurrence of the incident	
Measures taken, or intended to be taken, to rectify, limit or prevent any pollution of the environment which has been or may be caused by the emission	
The dates of any unauthorised emissions from the facility in the preceding 24 months.	
Name*	
Post	
Signature	

Date

<sup>\*</sup> authorised to sign on behalf of the operator

#### Schedule 6 – Interpretation

"abatement equipment" means that equipment dedicated to the removal of polluting substances from releases from the installation to air or water media.

"abnormal operation" means: any technically unavoidable stoppages, disturbances, or failures of the plant or the measurement devices. Abnormal operation starts as defined in condition 2.3.12 and ends as defined in condition 2.3.13. Abnormal operation is limited to 4 hours for a single occurrence and a total of 60 hours per year per line.

"accident" means an accident that may result in pollution.

"APC residues" means air pollution control residues

"application" means the application for this permit, together with any additional information supplied by the operator as part of the application and any response to a notice served under Schedule 5 to the EP Regulations.

"authorised officer" means any person authorised by the Environment Agency under section 108(1) of The Environment Act 1995 to exercise, in accordance with the terms of any such authorisation, any power specified in section 108(4) of that Act.

"BAT conclusions" means Commission Implementing Decision (EU) 2019/2010 of 12 November 2019 establishing the best available techniques (BAT) conclusions, under Directive 2010/75/EU of the European Parliament and of the Council, for Waste Incineration

"bottom ash" means ash falling through the grate or transported by the grate

"CEM" Continuous emission monitor

"CEN" means Commité Européen de Normalisation

"bi-annual" means twice per year with at least five months between tests;

"Commissioning" means testing of the new incineration plant that involves any operation of the furnace or as agreed with the Environment Agency.

Daily average emissions value means 'the average of at least 43 valid half hourly averages or for CO the average of at least 43 valid half hourly averages or 129 valid 10 min averages'

"dioxin and furans" means polychlorinated dibenzo-p-dioxins and polychlorinated dibenzofurans.

"disposal". Means any of the operations provided for in Annex I to Directive 2008/98/EC of the European Parliament and of the Council on waste.

"emissions to land" includes emissions to groundwater.

"EP Regulations" means The Environmental Permitting (England and Wales) Regulations SI 2016 No.1154 and words and expressions used in this permit which are also used in the Regulations have the same meanings as in those Regulations.

"emissions of substances not controlled by emission limits" means emissions of substances to air, water or land from the activities, either from the emission points specified in schedule 3 or from other localised or diffuse sources, which are not controlled by an emission limit.

"groundwater" means all water, which is below the surface of the ground in the saturation zone and in direct contact with the ground or subsoil.

'Hazardous property' has the meaning in Annex III of the Waste Framework Directive

"incineration line" means all of the incineration equipment related to a common discharge to air location.

"Industrial Emissions Directive" means DIRECTIVE 2010/75/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 24 November 2010 on industrial emissions

"ISO" means International Standards Organisation.

*'List of Wastes'* means the list of wastes established by Commission Decision 2000/532/EC replacing Decision 94/3/EC establishing a list of wastes pursuant to Article 1(a) of Council Directive 75/442/EEC on waste and Council Decision 94/904/EC establishing a list of hazardous waste pursuant to Article 1(4) of Council Directive 91/689/EEC on hazardous waste, as amended from time to time

"LOI" means loss on ignition a technique used to determine the combustible material by heating the ash residue to a high temperature

"MCERTS" means the Environment Agency's Monitoring Certification Scheme.

"PAH" means Poly-cyclic aromatic hydrocarbon, and comprises Anthanthrene, Benzo[a]anthracene, Benzo[b]fluoranthene, Benzo[b]naph(2,1-d)thiophene, Benzo[c]phenanthrene, Benzo[ghi]perylene, Benzo[a]pyrene, Cholanthrene, Chrysene, Cyclopenta[c,d]pyrene, Dibenzo[ah]anthracene, Dibenzo[a,i]pyrene Fluoranthene, Indo[1,2,3-cd]pyrene, Naphthalene

"PCB" means Polychlorinated Biphenyl. Dioxin-like PCBs are the non-ortho and mono-ortho PCBs listed in the table below.

"Pests" means Birds, Vermin and Insects.

"quarter" means a calendar year quarter commencing on 1 January, 1 April, 1 July or 1 October.

"recovery" means any of the operations provided for in Annex II to Directive 2008/98/EC of the European Parliament and of the Council on waste.

"start up" is any period, where the plant has been non-operational, until waste has been fed to the plant in a sufficient quantity to initiate steady-state conditions as described in the application or agreed in writing with the Environment Agency.

"shut down" is any period where the plant is being returned to a non-operational state as described in the application or agreed in writing with the Environment Agency.

"TOC" means Total Organic Carbon. In respect of releases to air, this means the gaseous and vaporous organic substances, expressed as TOC. In respect of Bottom Ash, this means the total carbon content of all organic species present in the ash (excluding carbon in elemental form).

'Waste code' means the six digit code referable to a type of waste in accordance with the List of Wastes and in relation to hazardous waste, includes the asterisk

"Waste Framework Directive" or "WFD" means Waste Framework Directive 2008/98/EC of the European Parliament and of the Council on waste

Where a minimum limit is set for any emission parameter, for example pH, reference to exceeding the limit shall mean that the parameter shall not be less than that limit.

Unless otherwise stated, any references in this permit to concentrations of substances in emissions into air means:

- (a) in relation to emissions from combustion processes, the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 3% dry for liquid and gaseous fuels, 6% dry for solid fuels; and/or
- (b) in relation to gases from incineration plants other than those burning waste oil, the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 11% dry.

For dioxins/furans and dioxin-like PCBs the determination of the toxic equivalence concentration (I-TEQ, & WHO-TEQ for dioxins/furans, WHO-TEQ for dioxin-like PCBs) stated as a release limit and/ or reporting requirement, the mass concentrations of the following congeners have to be multiplied with their respective toxic equivalence factors before summing. When reporting on measurements of dioxins/furans and dioxin-like PCBs, the toxic equivalence concentrations should be reported as a range based on: all congeners less than the detection limit assumed to be zero as a minimum, and all congeners less than the detection limit assumed to be at the detection limit as a maximum. However the minimum value should be used when assessing compliance with the emission limit value in table S3.1.

TEF schemes for dioxins and furans						
Congener	I-TEF	WHO-TEF				
	1990	2005	1997/8			
		Humans / Mammals	Fish	Birds		
Dioxins						
2,3,7,8-TCDD	1	1	1	1		
1,2,3,7,8-PeCDD	0.5	1	1	1		
1,2,3,4,7,8-HxCDD	0.1	0.1	0.5	0.05		
1,2,3,6,7,8-HxCDD	0.1	0.1	0.01	0.01		
1,2,3,7,8,9-HxCDD	0.1	0.1	0.01	0.1		
1,2,3,4,6,7,8-HpCDD	0.01	0.01	0.001	<0.001		
OCDD	0.001	0.0003	-	-		
Furans						
2,3,7,8-TCDF	0.1	0.1	0.05	1		
1,2,3,7,8-PeCDF	0.05	0.03	0.05	0.1		
2,3,4,7,8-PeCDF	0.5	0.3	0.5	1		
1,2,3,4,7,8-HxCDF	0.1	0.1	0.1	0.1		
1,2,3,7,8,9-HxCDF	0.1	0.1	0.1	0.1		
1,2,3,6,7,8-HxCDF	0.1	0.1	0.1	0.1		
2,3,4,6,7,8-HxCDF	0.1	0.1	0.1	0.1		
1,2,3,4,6,7,8_HpCDF	0.01	0.01	0.01	0.01		
1,2,3,4,7,8,9-HpCDF	0.01	0.01	0.01	0.01		
OCDF	0.001	0.0003	0.0001	0.0001		

Congener	WHO-TEF	WHO-TEF		
	2005	1997/8		
	Humans / mammals	Fish	Birds	
Non-ortho PCBs				
3,4,4',5-TCB (81)	0.0001	0.0005	0.1	
3,3',4,4'-TCB (77)	0.0003	0.0001	0.05	
3,3',4,4',5 - PeCB (126)	0.1	0.005	0.1	
3,3',4,4',5,5'-HxCB(169)	0.03	0.00005	0.001	
Mono-ortho PCBs				
2,3,3',4,4'-PeCB (105)	0.00003	<0.000005	0.0001	
2,3,4,4',5-PeCB (114)	0.00003	<0.00005	0.0001	

TEF schemes for dioxin-like PCBs				
Congener	WHO-TEF			
	2005	2005 1997/8		
	Humans /	Fish	Birds	
	mammals			
2,3',4,4',5-PeCB (118)	0.00003	<0.000005	0.00001	
2',3,4,4',5-PeCB (123)	0.00003	<0.000005	0.00001	
2,3,3',4,4',5-HxCB (156)	0.00003	<0.000005	0.0001	
2,3,3',4,4',5'-HxCB (157)	0.00003	<0.000005	0.0001	
2,3',4,4',5,5'-HxCB (167)	0.00003	<0.000005	0.00001	
2,3,3',4,4',5,5'-HpCB (189)	0.00003	<0.000005	0.00001	

<sup>&</sup>quot;year" means calendar year ending 31 December.

When the following terms appear in the waste code list in Schedule 2, table 2.2 or S2.3, for those tables, they have the meaning given below:

'hazardous substance' means a substance classified as hazardous as a consequence of fulfilling the criteria laid down in parts 2 to 5 of Annex I to Regulation (EC) No 1272/2008

'heavy metal' means any compound of antimony, arsenic, cadmium, chromium (VI), copper, lead, mercury, nickel, selenium, tellurium, thallium and tin, as well as these materials in metallic form, as far as these are classified as hazardous substances

#### 'PCBs' means

- polychlorinated biphenyls
- polychlorinated terphenyls
- monomethyl-tetrachlorodiphenyl methane, Monomethyl-dichloro-diphenyl methane, Monomethyldibromo-diphenyl methane
- any mixture containing any of the above mentioned substances in a total of more than 0,005 %by weight


'transition metals' means any of the following metals: any compound of scandium, vanadium, manganese, cobalt, copper, yttrium, niobium, hafnium, tungsten, titanium, chromium, iron, nickel, zinc, zirconium, molybdenum and tantalum, as well as these materials in metallic form, as far as these are classified as hazardous substances

'stabilisation' means processes which change the hazardousness of the constituents in the waste and transform hazardous waste into non-hazardous waste


'solidification' means processes which only change the physical state of the waste by using additives without changing the chemical properties of the waste

'partly stabilised wastes' means wastes containing, after the stabilisation process, hazardous constituents which have not been changed completely into non-hazardous constituents and could be released into the environment in the short, middle or long term.

### Schedule 7 – Site plan



#### This is the plan referred to in the standard rules SR2008No1 75kte



END OF PERMIT